



CCM RESTORATION RANGE WALL AND CEILING Data Sheet

Description:

CCM Restoration Range Wall and Ceiling is a high quality interior low sheen finish designed for use in living areas. Its application properties are formulated to give a good covering finish with excellent flow and leveling. Gloss level @60 degrees 5.5GU.

Physical Properties

Resin Type:	Modified Acrylic
Solvent:	Water
Colour:	White, and full range of tinted colours
Finish:	Low Sheen
Drying time:	1 hour @ 18°C
Recoat time:	2 hours @ 18°
Dry Film Thickness:	50µ minimum
No. of coats:	2, some colours may require a 3 rd coat
Theoretical Coverage:	12m ² /litre per coat to attain 50µ
Primer Needed:	For most substrates
Thinning & Cleaning:	Thin up to 5% with water, cleanup with water

Performance:

- Excellent adhesion to **CCM** primers and undercoats.
- Good coverage when correctly applied.
- Easy to apply.

Limitations:

- Do not apply when temperature is below or expected to fall under 10°C.
- Not recommended for use in toilets, bathrooms and kitchens. Use **CCM Acrylic Enamel** in these areas.
- More than 2 coats maybe necessary when applying over porous fillers and sealers.

Substrate Preparation:

All preparation and painting must conform to AS2311: The Painting of Buildings. Ensure all surfaces are clean, dry and dust free. Washing pre-painted surfaces with Sugar Soap is recommended. Old enamels and varnishes should be primed with **All Prime** or **CCM Oil based Wallboard Sealer**. Over new Wall Board prime with **CCM Easy Sand** or **CCM Acrylic Sealer Undercoat**.

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, Commercial Coating Manufacturers Ltd makes no representation as to the completeness and accuracy thereof.

In no event will Commercial Coating Manufacturers Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers.

The logo for the Restoration Range features a stylized black icon of a building with horizontal lines and two small squares at the base, representing windows or doors.

RESTORATION RANGE

Application:

CCM Restoration Range Wall and Ceiling may be applied by brush, roller, speed brush or spray. Thinning with water is only recommended for spray application.

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, Commercial Coating Manufacturers Ltd makes no representation as to the completeness and accuracy thereof.

In no event will Commercial Coating Manufacturers Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers.